

## MAX-MATIC 100 - 500 GPM (400-2000 l/min) Automatic

**MD18A**

**MD17A**

**\$925.00**

**6.5 lb (2.9kg)**

**9.0" (22.9cm)**



**MD18A** MAX-MATIC 100 PSI AUTOMATIC TIP 2.5" NH (65mm) - Automatic pressure control with a flow capacity of 100-500 gpm (400-2000 l/min). The nozzle operates at a standard 100 psi (7bar). The pattern adjusts from straight stream to a 120 degree wide fog. Further rotation opens the nozzle to flush 3/8" (10mm) debris without shutting down. Hardcoat anodized aluminum with rubber bumper. Standard inlet is 2.5" NH (65mm) rocker lug swivel.

**MD17A** MAX-MATIC 80 PSI - LOW PRESSURE VERSION – Same as MD18A above, but operates at a low pressure of approximately 80 psi (6bar).


**MD-ERP-18A**

**MD-ER-18A**

**\$1500.00**

**10 lbs (4.5kg)**

**10" (26cm)**



**MD-ERP-18A** 100 PSI (7bar) MAX-MATIC ELECTRIC REMOTE TIP Automatic pressure control with a flow capacity of 100-500 gpm (400-2000 l/min). The nozzle operates at a standard 100 psi (7bar). 2.5" NH (65mm) rigid rocker lug coupling is standard. For use on TFT RC monitors only.

**MD-ER-18A** - same as MD-ERP-18A except with 6 ft of non-terminated remote wire for custom installations. Does not have SMART STREAM technology