


# 1" (25mm) TWISTER® SERIES

10 & 24 or 10 & 40 GPM (37 & 90 or 37 & 150 l/min)

Dual Gallonage

The 1" (25mm) Twister is a selectable, dual gallonage, combination pattern nozzle, available in 3/4" (19mm) or 1" (25mm) threads and is designed for simplicity and durability. The rubber bumper provides a positive grip and protects the front end. Twisting the shaper from the "off" position produces the following settings: low flow straight stream, low flow narrow fog, high flow straight stream, then high flow fog. The Twister, with its optional colored pistol grip, is a rugged, economical nozzle that will accept the FJ-MX-D FOAMJET multi-expansion foam aspirating attachment.


**C1024**  
0.6 lb. (0.3kg)  
4" (10.2cm)



## 1" 10 and 24 GPM (25mm 37 and 90 l/min)

**C1024 TWISTER TIP** 3/4" GHT (19mm) - Dual gallonage nozzle with two flow settings of 10 and 24 gpm @ 100 psi (37 and 90 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. This tip only design has a twist "off" position for break-and-extend operations. 3/4" GHT (19mm) rigid thread is standard.


**D1024**  
**D1024-ID**  
0.6 lb. 0.3kg  
4" (10.2cm)



**D1024 TWISTER TIP** 1" NH (25mm) - Dual gallonage nozzle with two flow settings of 10 and 24 gpm @ 100 psi (37 and 90 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. This tip only design has a twist "off" position for break-and-extend operations. 1" NH (25mm) rigid thread is standard.

**-ID = 1.0" NPSH Threads.**


**DS1024**  
**DS1024-ID**  
1.5 lb. (0.7kg)  
6-1/4" (15.9cm)



**DS1024 TWISTER NOZZLE** 1" NH (25mm) - Dual gallonage nozzle with two flow settings of 10 and 24 gpm @ 100 psi (37 and 90 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. Quick-change rear valve seat, stainless steel shut-off ball and a twist "off" position for positive shut off. Rocker lug 1" NH (25mm) swivel is standard.

**-ID = 1.0" NPSH Threads.**

**DS1024P**  
**DS1024P-ID**  
1.9 lb. (0.9kg)  
6-1/4" (15.9cm)




**DS1024P TWISTER W/GRIP** 1" NH (25mm) - Dual gallonage nozzle with two flow settings of 10 and 24 gpm @ 100 psi (37 and 90 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. Quick-change rear valve seat, stainless steel shut-off ball and a twist "off" position for positive shut off. Pistol grip is mounted below the valve. Rocker lug 1" NH (25mm) swivel is standard.

**-ID = 1.0" NPSH Threads.**


## 1" 10 and 40 GPM (25mm 37 and 150 l/min)

**D1040**  
**D1040-ID**  
0.6 lb. (0.3kg)  
4" (10.2cm)




**D1040 TWISTER TIP** 1" NH (25mm) - Dual gallonage nozzle with two flow settings of 10 and 40 gpm @ 100 psi (37 and 150 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. This tip only design has a twist "off" position for break-and-extend operations. 1" NH (25mm) rigid thread is standard. **-ID = 1.0" NPSH Threads.**

**DS1040**  
**DS1040-ID**  
1.5 lb. (0.7kg)  
6-1/4" (15.9cm)



**DS1040 TWISTER NOZZLE** 1" NH (25mm) - Dual gallonage nozzle with two flow settings of 10 and 40 gpm @ 100 psi (37 and 150 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. Quick-change rear valve seat, stainless steel shut-off ball and a twist "off" position for positive shut off. Rocker lug 1" NH (25mm) swivel is standard. **-ID = 1.0" NPSH Threads.**

**DS1040P**  
**DS1040P-ID**  
1.9 lb. (0.9kg)  
6-1/4" (15.9cm)







**DS1040P TWISTER W/GRIP** 1" NH (25mm) - Dual gallonage nozzle with two flow settings of 10 and 40 gpm @ 100 psi (37 and 150 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. Quick-change rear valve seat, stainless steel shut-off ball and a twist "off" position for positive shut off. Pistol grip is mounted below the valve. Rocker lug 1" NH (25mm) swivel is standard. **-ID = 1.0" NPSH Threads.**

**-ID = 1.0" NPSH Threads.**




1" (25mm) TWISTER® SERIES  
10 & 24 GPM (37 & 90 l/min)

FoamJet Models for  
1" Twister Series - FJ-MX-D

Dual Gallonge 1" Nozzles				
	Nozzle Tip Only 3/4" GHT	Nozzle Tip Only	Nozzle w/Shutoff	Nozzle w/Shutoff & Pistol Grip
	100 psi 3/4" GHT Threads	C1024		
	100 psi NH Threads		D1024	DS1024
100 psi NPSH Threads		D1024-ID	DS1024-ID	DS1024P-ID

1" (25mm) TWISTER® SERIES  
10 & 40 GPM (37 & 150 l/min)

FoamJet Models for  
1" Twister Series - FJ-MX-D

Dual Gallonge 1" Nozzles			
	Nozzle Tip Only	Nozzle w/Shutoff	Nozzle w/Shutoff & Pistol Grip
	100 psi NH Threads	D1040	DS1040
	100 psi NPSH Threads	D1040-ID	DS1040-ID


## 1.5" (38mm) TWISTER® SERIES

20 & 60 or 20 & 95 GPM (75 & 230 or 75 & 360 l/min)

Dual Gallonage

The 1.5" (38mm) Twister is a selectable, dual gallonage, combination pattern nozzle available in 1.5" (38mm) threads and is designed for simplicity and durability. The rubber bumper provides a positive grip and protects the fixed metal fog teeth. Twisting the shaper from the "off" position produces the following settings: low flow straight stream, low flow narrow fog, high flow straight stream, then high flow fog. The Twister, with its optional colored pistol grip, is a rugged, economical nozzle that will accept the FJ-MX-F FOAMJET multi-expansion foam aspirating attachment.


**F2060**  
**F2060-IF**  
1.2 lb. (0.6kg)  
5-1/4" (13.3cm)



### 1.5" 20 and 60 GPM (38mm 75 and 230 l/min)


**F2060 TWISTER TIP** 1.5" NH (38mm) - Dual gallonage nozzle with two flow settings of 20 and 60 gpm @ 100 psi (75 and 230 l/min @ 7 bar). All lightweight materials, hardcoat aluminum. This tip only design has a twist "off" position for break-and-extend operations. 1.5" NH (38mm) rigid thread is standard.  
**-IF = 1.5" NPSH Threads.**

**FS2060**  
**FS2060-IF**  
2.4 lb. (1.1kg)  
7-3/8" (18.7cm)




**FS2060 TWISTER NOZZLE** 1.5" NH (38mm) - Dual gallonage nozzle with two flow settings of 20 and 60 gpm @ 100 psi (75 and 230 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. Quick-change rear valve seat, stainless steel shut-off ball and a twist "off" position for positive shut off. Rocker lug 1.5" NH (38mm) swivel is standard.  
**-IF = 1.5" NPSH Threads.**

**FS2060P**  
**FS2060P-IF**  
2.6 lb. (1.2kg)  
7-3/8" (18.7cm)



**FS2060P TWISTER W/GRIP** 1.5" NH (38mm) - Dual gallonage nozzle with two flow settings of 20 and 60 gpm @ 100 psi (75 and 230 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. Quick-change rear valve seat, stainless steel shut-off ball and a twist "off" position for positive shut off. Pistol grip is mounted below the valve. Rocker lug 1.5" NH (38mm) swivel is standard.  
**-IF = 1.5" NPSH Threads.**


**F2095**  
**F2095-IF**  
1.2 lb. (0.6kg)  
5-1/4" (13.3cm)



### 1.5" 20 and 95 GPM (38mm 75 and 360 l/min)


**F2095 TWISTER TIP** 1.5" NH (38mm) - Dual gallonage nozzle with two flow settings of 20 and 95 gpm @ 100 psi (75 and 360 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. This tip only design has a twist "off" position for break-and-extend operations. 1.5" NH (38mm) rigid thread is standard.  
**-IF = 1.5" NPSH Threads.**

**FS2095**  
**FS2095-IF**  
2.4 lb. (1.1kg)  
7-3/8" (18.7cm)



**FS2095 TWISTER NOZZLE** 1.5" NH (38mm) - Dual gallonage nozzle with two flow settings of 20 and 95 gpm @ 100 psi (75 and 360 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. Quick-change rear valve seat, stainless steel shut-off ball and a twist "off" position for positive shut off. Rocker lug 1.5" NH (38mm) swivel is standard.  
**-IF = 1.5" NPSH Threads.**




**FS2095P**  
**FS2095P-IF**  
2.6 lb. (1.2kg)  
7-3/8" (18.7cm)



**FS2095P TWISTER W/GRIP** 1.5" NH (38mm) - Dual gallonage nozzle with two flow settings of 20 and 95 gpm @ 100 psi (75 and 360 l/min @ 7bar). All lightweight materials, hardcoat anodized aluminum. Quick-change rear valve seat, stainless steel shut-off ball and a twist "off" position for positive shut off. Pistol grip is mounted below the valve. Rocker lug 1.5" NH (38mm) swivel is standard.  
**-IF = 1.5" NPSH Threads.**




1.5" (38mm) TWISTER® SERIES  
20 & 60 GPM (75 & 230 l/min)

FoamJet Models for  
1.5" Twister Series - FJ-MX-F

<b>Dual Gallonage 1.5" Nozzles</b>			
	Nozzle Tip Only	Nozzle w/Shutoff	Nozzle w/Shutoff & Pistol Grip
	100 psi NH Threads	F2060	FS2060
100 psi NPSH Threads	F2060-IF	FS2060-IF	FS2060P-IF

1.5" (38mm) TWISTER® SERIES  
20 & 95 GPM (75 & 360 l/min)

FoamJet Models for  
1.5" Twister Series - FJ-MX-F

<b>Dual Gallonage 1.5" Nozzles</b>			
	Nozzle Tip Only	Nozzle w/Shutoff	Nozzle w/Shutoff & Pistol Grip
	100 psi NH Threads	F2095	FS2095
100 psi NPSH Threads	F2095-IF	FS2095-IF	FS2095P-IF